

Highlights:

- Stores up to 42 units of 19" Equipment
- Integrated ventilation grid on top
- 50 mm Wheels + leveling feet included
- Removable sides for easy installing & cabling
- Punched square holes for use with snap-in cage nuts
- Front and rear in depth adjustable 19" profiles (max 740 mm)
- Tempered glass door with keylock
- Reversible door position
- Swing handle with cylinder lock
- Width of 800 mm for convenient installation and maintenance
- Available space on sides for cable management systems and accessories

Product information:

The SPR8842 is a professional 19" rack compliant to the ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. A cold rolled steel 2 mm thick frame and 1,2 mm thick plates provide a solid and stable construction making it suitable for heavy equipment, storing up to 42 units inside. The SPR8842 comes fully assembled including 50 mm wheels for easy moving and adjustable feet for fixing and levelling once correctly positioned. The 19" mounting profile with punched square holes for use with snap-in cage nuts in combination with the printed unit measurement indicators ensure an easy fitting of the equipment. Adjustable 19 " profiles provide great flexibility for installing equipment depending on its depth.

The SPR8842 comes with a tempered glass front door and steel rear door. The swing handle with cylinder lock safely locks the equipment inside. The width of 800 mm offers additional space for the installation of accessories and cable management systems, while guaranteeing an optimal convenience for installation and maintenance of the equipment.



Product Features:

| | | |
|-------------------------------------------|----------|----------------------------------------------------------|
| Unit height | | 42 HE |
| Dimensions | | 31.50 x 78.15 (80.91) x 31.50 " (W x H (incl. feet) x D) |
| Max. usable depth | | 29.13 " |
| Wheel | Diameter | 1.97 " |
| Colours | | Black (RAL9004) |
| Accessories | Included | 4 x Key for sidepanel lock |
| | | 1 x Allen key |
| | | 1 x Levelling feet |
| | | 4 x Key for front/back door |
| | | 20 x KM600 |
| | | 20 x KS600 |
| | Optional | KS600 - M6 x 16 mm bolt DIN7985 Black |
| | | SPR10CS - Rack interconnection slot |
| | | KM600 - M6 Cage nuts |
| | | SPR80LR - L-Rail pair |
| | | SPR80FS - Fixed shelf |
| | | SPR80SS - Sliding shelf |
| | | SPR80RF - Cooling roof fan unit (230V) |
| Static load capacity (adjustable feet) | | 1763.70 lb |
| Dynamic load capacity (transport castors) | | 881.85 lb |
| Weight | | 264.55 lb |

Variants:

- SPR8842/B - Black version - 800mm width

