



Highlights:

- · null
- · null
- Flexible structure for system integration & connectivity
- · Wide variation of compatible modules available
- Pre-threaded mounting profile for easy assembly
- Structured and scratch resistant black powder coating
- · Removable cable gland for D-size connectors at choice
- · Stores 4 units of CASY modules
- · Long cable gland provided





The aluminum construction features pre-threaded hole inserts allowing module installation with a maximum of 4 units with a built-in depth up to 60 mm. It is fitted with a cable gland with strain relief accepting diameters in a range of 9 to 16 mm, which can be removed for assembly of a D-sized connector type (e.g. PowerCON). The sides are constructed out of cold-rolled steel protected with rubber shock bumpers perfect for all use and abuse. Modules can be fixed inside the unit using the included M3 screws. The overall construction is finished in a black (RAL9004) structured and scratch-resistant powder coating.





Product Features:

Module	Units	4 x front side
Dimensions		6.50 x 4.27 x 3.36 " (W x H x D)
Weight		1.12 lb
Construction		Alu extrusion with steel side panels
		Protected with rubber shock bumpers perfect for all use and abuse
Connection		1 x D-size hole
		9 ~ 16 mm cable gland (standard)
Finish		Structured powder coating
Colours		Black (RAL9004)
Max. usable depth		2.36 "

Variants:	
· CASY044S/B - Black version	
MONI CACVOAAC 00/02/2022 17:12 LITC	

