

DOTQ

Portable and cable free accent battery light



DOTQ is an ultra-compact, wireless, battery, LED accent luminaire designed to complement uplighting both inside a room, and outside. Its compact form factor and chrome finish allow it to be used anywhere that needs a "little lift" to finish off the perfect event design.



DOTQ-PACK Bundle includes:

- ABS case
- 6 fixtures
- charging station
- 6 top hats
- magnetic frost filters
- IR controller
- eye bolts, suction cups, yokes.

FEATURES

- Even, powerful saturated and pastel colors from single 15W RGBW LED.
- Chrome Finish, ultra-compact size and IP65 rating for incredible versatility.



LIGHT SOURCE

1x15W RGBW LED



BATTERY

Up to 6 hours in full-on white



IP RATE

Waterproof structure IP 65/54

PHOTO GALLERY & APPLICATIONS



DOTQ-PACK

DOTQ

Portable and cable free accent battery light




DOTQ Technical Specification


LIGHT SOURCE		IR:	
Source:	1x15WRGBW LEDs	IR:	IR remote controller for simple control, addressing and settings
Luminous Flux:	203lm	ELECTRONICS	
Lux:	467lux@3m Full	Dimmer:	Linear 0~100% electronic dimmer
OPTICS		Strobe/Shutter:	1-25Hz, electronic
Beam Angle:	15°	BATTERY	
Field Angle:	23°	Battery:	11,1VLithium
Additional Optics:	Magnetic Frost filter included for wider diffusion	Autonomy in color change mode, up to:	16h
COLOR SYSTEM		Autonomy in permanent white full-on, up to:	6h
Color Mixing:	RGBW/FC	Recharge Time:	3h/max
Color Wheel:	Virtual color wheel with presets	PHYSICAL	
BODY		IP:	For temporary outdoor use -IP65 (front) - IP54 (bottom)
Tilt Angle:	Adjustable foot support for tilt regulation (up to 20°)	Dimensions (WxHxD):	88x88x63mm / 3.46"x3.46"x2.48"
CONTROL		Weight:	0,6kg / 1.32lbs
Protocols:	W-DMX		
W-DMX:	Included, Lumen Radio CRMX receiver		



TECHNICAL DRAWING



PHOTOMETRIC DATA



APPROVED



prolightsamerica.com



info@prolightsamerica.com
www.prolightsamerica.com

Distributed by



A.C. Lighting Inc.
Tel: +1 416-255-9494
Fax: +1 416-255-3514

northamerica@aclighting.com
www.aclighting.com